

Data Sheet | Item Number: 870-404

Jumper; 4-way; insulated; light gray

<https://www.wago.com/870-404>



Color: ■ light gray

Electrical data

Ratings per IEC/EN

Rated current 18 A

Ex information

Rated current (Ex e II) 13.5 A

Physical data

Width 19 mm / 0.748 inches

Height 2.5 mm / 0.098 inches

Jumper assignment 1-2-3-4

Material data

Note (material data)

[Information on material specifications can be found here](#)

Color light gray

Fire load 0.022 MJ

Weight 2 g

Commercial data

eCl@ss 10.0 27-14-11-40

eCl@ss 9.0 27-14-11-40

ETIM 8.0 EC000489

ETIM 7.0 EC000489

PU (SPU) 25 (25) pcs

Packaging type Box

Country of origin DE

GTIN 4066966273311

Customs tariff number 85366990990

Environmental Product Compliance

RoHS Compliance Status Compliant, No Exemption

Downloads

Documentation

Additional Information		
Technical Section	pdf 2240.62 KB	↓

Bid Text				
870-404	19.02.2019	xml 2.51 KB		↓
870-404	04.01.2018	doc 23.50 KB		↓



CAD/CAE-Data

CAD data	
2D/3D Models 870-404	↓

CAE data	
EPLAN Data Portal 870-404	↓
WSCAD Universe 870-404	↓
ZUKEN Portal 870-404	↓

Installation Notes

Commoning



Commoning with push-in type jumper bars:
Two parallel jumper slots are accommodated in one terminal block.

Push jumper bars down firmly until fully inserted. When using multipole bars, push alternately on the right and then left side until installed.
Push-in type jumper bars 1 – 3 – 5 – 7 or 1 – – 4 – – 7 upon request